



BAROLI 02

Battery Powered Digital Pressure Gauge

Stainless Steel Sensor

class 0.1

Nominal pressure

from 0 ... 100 mbar up to 0 ... 600 bar

Special characteristics

- ▶ rotatable housing
- ▶ 2-line LC display
- 4.5-digit 7-segment display
- 6-digit 14-segment additional display

Functions

- ▶ min / max function with reset function
- ▶ offset and end point calibration
- ▶ setting the pressure unit
(bar, mbar, psi, InHg, cmHg, mmHg,
hPa, kPa, MPa, mH₂O, InH₂O)
- ▶ switch-off automatic

The battery-powered digital pressure gauge BAROLI 02 enables a local displaying of values, satisfying the highest demands for accuracy and long-term stability. The pressure gauge may be applied in all media compatible with the stainless steel used; it shows an excellent robustness and a high overpressure protection.

The BAROLI 02 display housing is rotatable, thus ensuring an easy reading even under unfavourable mounting conditions.

Additional functions:

changing the unit, displaying min / max values, calibrating of offset and the span, configuring the automatic switching-off

Preferred areas of use are



Plant and machine engineering
Pneumatics / hydraulics
Measurement technology
Calibration and test purposes



Laboratory techniques



Environmental engineering
(water – sewage – recycling)



BAROLI 02

Digital Pressure Gauge

Technical Data

Input pressure ranges

Nominal pressure gauge [bar]	0.10	0.16	0.25	0.40	0.60	1	1.6	2.5	4	6
Nominal pressure abs. [bar]	-	-	-	0.40	0.60	1	1.6	2.5	4	6
Overpressure [bar]	0.5	1	1	2	5	5	10	10	20	40
Burst pressure [bar]	1.5	1.5	1.5	3	7.5	7.5	15	15	25	50
Nominal pressure gauge / absolute [bar]	10	16	25	40	60	100	160	250	400	600
Overpressure [bar]	40	80	80	105	105	210	600	1050	1050	1250
Burst pressure [bar]	50	120	120	210	210	420	1000	1250	1250	1250
Vacuum pressure	-1 ... 0 bar, overpressure: 5 bar, burst pressure: 7.5 bar other vacuum ranges on request									
Vacuum resistance	$P_N \geq 1$ bar: unlimited vacuum resistance; $P_N < 1$ bar: on request									

Performance

Accuracy ¹	nominal pressure ≥ 0.4 bar: $\leq \pm 0.125\%$ FSO BFSL nominal pressure < 0.4 bar: $\leq \pm 0.25\%$ FSO BFSL		
Measuring rate	5/sec		
Long term stability	$\leq \pm 0.1\%$ FSO / year at reference conditions		

¹ accuracy according to IEC 61298-2 – minimum value setting (non-linearity, hysteresis, repeatability)

Thermal effects (offset and span)

Nominal pressure P_N [bar]	-1 ... 0	≤ 0.40	> 0.40
Tolerance band [% FS]	$\leq \pm 0.75$	$\leq \pm 1$	$\leq \pm 0.75$
in compensated range [°C]	-20 ... 85 °C	0 ... 70 °C	-20 ... 85 °C

Permissible temperatures

Permissible temperatures	medium: -20 ... 85 °C	environment: -20 ... 70 °C	storage: -30 ... 80 °C
--------------------------	-----------------------	----------------------------	------------------------

Mechanical stability

Vibration	5 g RMS / 10 ... 2000 Hz	according to DIN EN 60068-2-6
Shock	500 g / 1 msec half sine	according to DIN EN 60068-2-27

Materials

Pressure port / Housing	stainless steel 1.4404 (316 L)
Display housing	PA 6.6, polycarbonate
Seals (media wetted)	FKM
Diaphragm	stainless steel 1.4435 (316 L)
Media wetted parts	pressure port, seals, diaphragm


Miscellaneous

Display	LC display, visible range 40 x 30 mm; 4.5-digit 7-segment-display, digit height 11 mm, range of indication ± 19999 ; 6-digit 14-segment additional display, digit height 7.5 mm
Electromagnetic compatibility	emission and immunity according to EN 61326
Supply	3.6 V Lithium battery; 2 pieces (type 1/2 AA)
Data storage	EEPROM (non-volatile)
Ingress protection	IP 65
Installation position	any ²
Weight	approx. 300 g
AD-converter solution	14 Bit
Operational life of battery	standby mode: approx. 5 years
Mech. operational life	100 million load cycles
CE-conformity	EMC Directive: 2014/30/EU Pressure Equipment Directive: 2014/68/EU (Modul A) ³

² The digital pressure gauge is calibrated in a vertical position with the pressure connection down. If this position is changed on installation there can be slight deviations in the zero point for devices with stainless steel sensor and pressure range $P_N \leq 1$ bar.

³ This directive is only valid for devices with maximum permissible overpressure > 200 bar.

Dimensions (in mm)



⇒ for nominal pressure $P_N > 60$ bar increases the length of devices by 9 mm!

Ordering code BAROLI 02

BAROLI 02	<input type="text"/> <input type="text"/> - <input type="text"/> <input type="text"/> <input type="text"/> - <input type="text"/> - <input type="text"/> <input type="text"/> - <input type="text"/> K <input type="text"/> - <input type="text"/> <input type="text"/> - <input type="text"/>
Pressure	
gauge	M 0 E
absolute ¹	M 0 F
Input	[bar]
0.10 ¹	1 0 0 0
0.16 ¹	1 6 0 0
0.25 ¹	2 5 0 0
0.40	4 0 0 0
0.60	6 0 0 0
1.0	1 0 0 1
1.6	1 6 0 1
2.5	2 5 0 1
4.0	4 0 0 1
6.0	6 0 0 1
10	1 0 0 2
16	1 6 0 2
25	2 5 0 2
40	4 0 0 2
60	6 0 0 2
100	1 0 0 3
160	1 6 0 3
250	2 5 0 3
400	4 0 0 3
600	6 0 0 3
-1 ... 0	X 1 0 2
customer	9 9 9 9
	consult
Accuracy	[BFSL]
standard for p _N ≥ 0.4 bar	0.125 %
standard for p _N < 0.4 bar	0.250 %
customer	9 9
Mechanical connection	
G1/2" EN 837	2 0 0
G1/4" EN 837	4 0 0
1/2" NPT	N 0 0
1/4" NPT	N 4 0
customer	9 9 9
	consult
Seals	
FKM	1
customer	9
	consult
Pressure port	
stainless steel 1.4404 (316L)	1
customer	9
	consult
Diaphragm	
stainless steel 1.4435 (316L)	1
customer	9
	consult
Front foil	
standard	1
neutral	N
customer	9
	consult
Special version	
standard	0 0 0
customer	9 9 9
	consult

¹ absolute pressure possible from 0.4 bar