



LMK 351

Screw-in Transmitter

Ceramic Sensor

accuracy according to IEC 61298-2:
standard: 0.35% FSO
option: 0.25% FSO

Nominal pressure

from 0 ... 40 mbar up to 0 ... 20 bar

Output signal

2-wire: 4 ... 20 mA
others on request

Product characteristics

- ▶ pressure port PVDF or PP-HT for aggressive media
- ▶ pressure port G 1 1/2" for pasty and polluted media
- ▶ diaphragm ceramics Al₂O₃ 99.9 %



Optional versions

- ▶ IS-version
Ex ia = intrinsically safe for gases and dust
- ▶ customer specific versions



The screw-in transmitter LMK 351 has been designed for measuring small system pressure and level measurement in container. The LMK 351 is based on an own-developed capacitive ceramic sensor element. Usage in viscous and pasty media is possible because of the flush mounted sensor.

For the usage in aggressive media a pressure port in PVDF is available. An intrinsically safe version completes the range of possibilities.

Preferred areas of use are

-  Plant and machine engineering
-  Environmental engineering
(water – sewage – recycling)


Preferred used for

-  Fuel and oil
-  Viscous and pasty media



Pressure ranges																
Nominal pressure	[bar]	0.04	0.06	0.1	0.16	0.25	0.4	0.6	1	1.6	2.5	4	6	10	16	20
Level	[mH ₂ O]	0.4	0.6	1	1.6	2.5	4	6	10	16	25	40	60	100	160	200
Overpressure	[bar]	2	2	4	4	6	6	8	8	15	25	25	35	35	45	45
Permissible vacuum	[bar]	-0.2		-0.3		-0.5				-1						
Output signal / Supply																
Standard	2-wire: 4 ... 20 mA / V _S = 9 ... 32 V _{DC}															
Option IS-version	2-wire: 4 ... 20 mA / V _S = 14 ... 28 V _{DC}															
Performance																
Accuracy ¹	standard: ≤ ± 0.35 % FSO option for p _N ≥ 0.6 bar: ≤ ± 0.25 % FSO															
Permissible load	R _{max} = [(V _S – V _{S min}) / 0.02 A] Ω															
Influence effects	supply: 0.05 % FSO / 10 V										load: 0.05 % FSO / kΩ					
Long term stability	≤ ± 0.1 % FSO / year at reference conditions															
Turn-on time	700 msec															
Mean measuring time	5/sec															
Response time	mean response time: ≤ 200 msec										max. response time: 380 msec					
¹ accuracy according to IEC 61298-2 - limit point adjustment (non-linearity, hysteresis, repeatability)																
Thermal effects (offset and span)																
Tolerance band	≤ ± 1 % FSO															
In compensated range	-20 ... 80 °C															
Permissible temperatures																
Permissible temperatures ²	medium: -40 ... 125 °C electronics / environment: -40 ... 85 °C storage: -40 ... 100 °C															
² for pressure port in PVDF the operation medium temperature is -30 ... 60 °C and in PP-HT 0 ... 60 °C																
Electrical protection																
Short-circuit protection	permanent															
Reverse polarity protection	no damage, but also no function															
Electromagnetic compatibility	emission and immunity according to EN 61326															
Mechanical stability																
Vibration	20 g RMS / 10 ... 2000 Hz										according to DIN EN 60068-2-6					
Shock	500 g / 1 msec half sine										according to DIN EN 60068-2-27					
Materials (media wetted)																
Pressure port / housing	standard: stainless steel 1.4404 (316L) option: PVDF (p _{max} = 20 bar @ t _{max} = 60 °C) PP-HT (p _{max} = 10 bar @ t _{max} = 60 °C)															
Option compact field housing	stainless steel 1.4301 (304); cable gland M12x1.5, brass, nickel plated (clamping range 2 ... 8 mm)															
Seals	FKM -40 ... 125 °C FFKM -15 ... 125 °C EPDM -40 ... 125 °C															
Diaphragm	ceramics Al ₂ O ₃ 99.9 %															
Media wetted parts	pressure port, seals, diaphragm															
Explosion protection																
Approval DX14-LMK 351	IBExU05ATEX1070 X stainless steel-pressure port with connector/cable outlet: zone 0: II 1G Ex ia IIC T4 Ga zone 20: II 1D Ex ia IIIC T110 °C Da plastic-pressure port with connector/cable outlet: zone 0/1: II 1/2G Ex ia IIC T4 Ga/Gb zone 20/21: II 1/2D Ex ia IIIC T110 °C Da/Db															
Safety technical maximum values	U _i = 28 V, I _i = 93 mA, P _i = 660 mW, C _i = 14 nF, L _i ≈ 0 μH, C _{gnd} = 27 nF															
Max. permissible temperature for environment	in zone 0: -20 ... 60 °C for p _{atm} 0.8 bar up to 1.1 bar zone 1 and higher: -25 ... 70 °C															
Connecting cables (by factory)	cable capacity: signal line / shield also signal line / signal line: 220 pF/m cable inductance: signal line / shield also signal line / signal line: 1.5 μH/m															
Miscellaneous																
Current consumption	max. 21 mA															
Weight	approx. 200 g															
Installation position	any															
Operational life	100 million load cycles															
CE-conformity	EMV-directive: 2014/30/EU															
ATEX Directive	2014/34/EU															
Wiring diagrams																

2-wire-system (current)




Pin configuration

Electrical connection	ISO 4400	Binder 723 (5-pin)	M12x1 (4-pin)	compact field housing	cable colours (IEC 60757)
Supply +	1	3	1	IN +	WH (white)
Supply -	2	4	2	IN -	BN (brown)
Shield	ground pin \oplus	5	4	\oplus	GNYE (green-yellow)


Electrical connections (dimensions in mm)

standard




ISO 4400
(IP 65)


options




Binder series 723 5-pin
(IP 67)




M12x1 4-pin
(IP 67)



cable outlet with
PVC cable
(IP 67) ³



cable outlet, cable with
ventilation tube
(IP 68) ⁴




compact field housing
(IP 67) ⁵

³ standard: 2 m PVC cable without ventilation tube (permissible temperature: -5 ... 70 °C)


⁴ different cable types and lengths available, permissible temperature depends on kind of cable

⁵ not possible in combination with pressure port made of PVDF or PP-HT

Dimensions (mm / in)



G1 1/2" flush (DIN 3852)
stainless steel



G1 1/2" flush (DIN 3852)
PVDF / PP-HT ⁶

⁶ not possible in combination with compact field housing

© 2025 BD|SENSORS GmbH – The specifications given in this document represent the state of engineering at the time of publishing. We reserve the right to make modifications to the specifications and materials.

Ordering code LMK 351

LMK 351

□□□ - □□□□ - □ - □ - □□□ - □□□ - □ - □ - □ - □□□

Pressure									
	in bar	4	7	0					
	in mH ₂ O	4	7	1					
Input									
	[mH ₂ O]	[bar]							
	0.4	0.04	0	4	0	0			
	0.6	0.06	0	6	0	0			
	1.0	0.10	1	0	0	0			
	1.6	0.16	1	6	0	0			
	2.5	0.25	2	5	0	0			
	4.0	0.40	4	0	0	0			
	6.0	0.60	6	0	0	0			
	10	1.0	1	0	0	1			
	16	1.6	1	6	0	1			
	25	2.5	2	5	0	1			
	40	4.0	4	0	0	1			
	60	6.0	6	0	0	1			
	100	10	1	0	0	2			
	160	16	1	6	0	2			
	200	20	2	0	0	2			
	customer		9	9	9	9			consult
Output									
	4 ... 20 mA / 2-wire		1						
	intrinsic safety 4 ... 20 mA / 2-wire		E						
	customer		9						consult
Accuracy									
	standard:	0.35 % FSO	3						
	option for p _N ≥ 0.6 bar:	0.25 % FSO	2						
	customer		9						consult
Electrical connection									
	male and female plug ISO 4400		1	0	0				
	male plug Binder series 723 (5-pin)		2	0	0				
	cable outlet with PVC cable (IP67) ¹		T	A	0				
	cable outlet,								
	cable with ventilation tube (IP68) ²		T	R	0				
	male plug M12x1 (4-pin) / metal		M	1	0				
	compact field housing								
	stainless steel 1.4301 (304) ³		8	5	0				
	customer		9	9	9				consult
Mechanical connection									
	G1 1/2" DIN 3852 with								
	flush sensor		M	0	0				
	customer		9	9	9				consult
Seal									
	FKM		1						
	EPDM		3						
	FFKM		7						
	customer		9						consult
Pressure port									
	stainless steel 1.4404 (316L)		1						
	PVDF (p _{max} = 20 bar) ⁴		B						
	PP-HT (p _{max} = 10 bar) ⁴		R						
	customer		9						consult
Diaphragm									
	ceramics Al ₂ O ₃ 99.9 %		C						
	customer		9						consult
Special version									
	standard		0	0	0				
	customer		9	9	9				consult

¹ standard: 2 m PVC cable without ventilation tube (permissible temperature: -5 ... 70 °C); others on request

² code TR0 = PVC cable, cable with ventilation tube available in different types and lengths; cable not included in the price

³ not possible in combination with pressure port made of PVDF or PP-HT

⁴ not possible in combination with compact field housing; for pressure port in PVDF the operation medium temperature is -30 ... 60 °C and in PP-HT 0 ... 60 °C